

basic assembly and equipment

types

TD-80
TD-80 S
TD-80 SII
TTS II (compactor)
TDL (ground-hole)

equipment

grafen	130 mm
spade	150 mm
spade	200 mm
shovel	
scraper	150 mm
scraper	200 mm
scraper	250 mm
delta chisel	100 mm
delta chisel	120 mm
flat chisel	25 mm
flat chisel	40 mm
point chisel	
dovetail scraper	150/250 mm
dovetail scraper	200/300 mm
compactor plate (TTS)	
plant hole digger (TDL)	170 mm
plant bale spade (TTS II)	200 mm
plant bale spade (TTS II)	300 mm
connecting tube	10m with quick-connecting

changing reserved



application fields

underground working:

trial trenches of smallest dimension trial holes,
undermining works,

smallest excavations, trenching works at
inaccessible parts,

compacting of small trenches, removing of loosable
surfaces (concrete, gravel, clay, grass)

building construction:

removing of cement rendering, striking off plaster,
stripping off bitumen layers,

restoration of old constructions, (removing
carpets, wood, wallpaper, tiles)

gardening and landscaping:

excavating of plants, loosening of foothpaths and
pavements, cutting of roots, removing of bark and
branches,

digging foundation pits, raising of path slabs,
removing exactly sward

technical data

type	handle (cm)	air vol. (l/min.)	no. of strikes (n/min)	weight (kg)
TD-80	80	150	3.500	2,6
TD-80 S	80	230	3.100	2,9
TD-80 SII	80	300	2.300	4,0
TTS II	80	450	1.800	9,5
TDL	80	450	1.800	10,5

05.10.2005

BSB

machines & vehicles

> **Jack the Digger** <

pneumatic shovel TD
pneumatic spade TD
pneumatic chisel TD
mini compactor TTS
ground-hole digger TDL



functioning

Due the construction and ergonomic design is „Jack the Digger“ a working tool which enables a rational working and a simultaneous reduction of the burden of the personnel.

The striking mechanism working in „Jack the Digger“ can be switched on as required so that work which had been performed in former times with 2 tools (pick and shovel or spade and chisel) can now be accomplished easier and faster with only one device.

In principal is „Jack the Digger“ being inserted as a traditional shovel, spade or chisel. If now the circumstances require the application of a device for breaking up the ground ergonomically, the striking mechanism can be activated by means of a release knob and the work can be continued without interruption.



Jack the Digger TD-80 S



Due to the quick changing device can „Jack the Digger“ be changed with just one handhold to a light compressed air pick, compressed air spade, compressed air scraper, compactor, rinsing device, chisel or point.



TDL - ground-hole

Jack the Digger pneumatic shovel

For sales ask your distributor:

Tasty[®] Plant Sales **LIMITED**

Telephone: +44 (0) 845 677 4444

Mobile: +44 (0) 785 035 2426

Email: info@tastyplant.co.uk

Paperstock House

Amersham Road

Chalfont St Giles

Bucks. HP8 4RU

BSB

machines & vehicles

Tel +49 (030) 52 695-544

Fax +49 (030) 52 695-546

Vulkanstraße 13,

D-10367 Berlin / Germany

mail@tastytool.com

www.tastytool.com

